# Wall Speaker


# **AUDAC**

#### Features

- Powerful 2 way wall speaker
- True-to-nature sound reproduction
- Available in 3 different colours
- Vertical or horizontal mounting
- Mounting bracket is included
- Easy installation
- Aluminium grill
- Adjustable power tapping

### Applications

- Wide variation of indoor applications
- Private houses
- Halls, Pubs
- Restaurants
- Stores
- Warehouses



They WX802 has a 8 1/4" low frequency loudspeaker and a 1" dome tweeter and is built in a synthetic enclosure which makes the speaker suitable for all purposes.

The speaker is suitable for standard home indoor installations to specialized indoor design appliances.

Due to the construction, the speaker can be mounted vertically or horizontally, using the included wall bracket.

This loudspeaker is available in three colours: white, black and silver, and is standard delivered with a wall fixig bracket in the same colour as the speaker.

By means of a recessed adjuster screw at the rear the power can be set in 3 adjustable steps of impedance for 100V and 1 step for 16 Ohm standard low impedance applications.

- 60 Watt, 30 Watt, 15 Watt @ 100V
- 70 Watt @ 16 Ohm



## **▶** Specifications

SYSTEM SPECIF	ICATIONS		
Max. power		140 W	
RMS power		70 W	
Power line transformer 1		60 W / 165 Ohm	
Power line transformer 2		30 W / 330 Ohm	
Power line transformer 3		15 W / 660 Ohm	
Frequency response -3dB		60 Hz - 17 KHz	
Frequency response -10dB		50 Hz - 20 KHz	
Crossover frequency		2.4 KHz	
Sound pressure W/1m		89 dB	
Sound pressure max W / 1m		108 dB	
Impedance		16 Ohm	
Crossover		Passive built-in	
Horizontal coverage		100°	
Vertical coverage		100°	
PRODUCT FEATI	JRES		
Dimensions (Width x Height x Depth)		270 x 360 x 215 mm	
Weight net		7.5 Kg	
Drivers	HF	1"	
	LF	8 1/4"	
Construction		ABS housing	
Mounting		Mounting bracket	
Front finish		Aluminium grill	
Connectors		Cable clamps	
Colour		White (RAL 9010)	WX802/W
		Black (RAL 9005)	WX802/B
		Silver (RAL 9006)	WX802/S
SHIPPING & ORD	ERING		
Packaging		Carton box	
Shipping weight & volume		15 Kg - 0.0636 Cbm	
Accessory included		Mounting bracket	

\*AUDAC reserves the right to change specifications without notice: this is part of our policy to continually improve our product