

DSP PARAMETER LD STINGER G3 SERIES



		Stinger 8G3 SAT	Stinger 8G3 FR	Stinger 8G3 MON	Stinger 8G3 FLT
GAIN	dB	0	0	0	0
Delay	Time (ms)	0	0	0	0
High Pass	Frequency [Hz]	95 Hz	50 Hz	70 Hz	50 Hz
	Slope [Bw]	24 dB/oct BW	24 dB/oct BW	24 dB/oct BW	24 dB/oct BW
Low Pass	Frequency				
	Slope				
PEQ1	Gain [dB]	+ 3 dB	+ 3 dB	+ 2 dB	+ 4 dB
	Frequency [Hz]	65 Hz	55 Hz	65 Hz	65 Hz
	Slope [Bw]	1	0,7	1	0,7
PEQ2	Gain [dB]	-3 dB	+8 dB	-3 dB	-3 dB
	Frequency [Hz]	500 Hz	65 Hz	500 Hz	500 Hz
	Slope [Bw]	0,6	1	0,6	0,6
PEQ3	Gain [dB]	-4 dB	-3 dB	-4 dB	-4 dB
	Frequency [Hz]	1400 Hz	500 Hz	1400 Hz	1400 Hz
	Slope [Bw]	2	0,6	2,4	2,4
PEQ4	Gain [dB]	-2 dB	-4 dB	-2 dB	+ 2 dB
	Frequency [Hz]	2600 Hz	1400 Hz	6800 Hz	5500 Hz
	Slope [Bw]	4	2	4	4
PEQ5	Gain [dB]	-2 dB	-2 dB	-6 dB	-2 dB
	Frequency [Hz]	6800 Hz	2600 Hz	18000 Hz	6800 Hz
	Slope [Bw]	2	4	0,6	2
PEQ6	Gain [dB]	+ 3 dB	-2 dB		
	Frequency [Hz]	16000 Hz	6800 Hz		
	Slope [Bw]	0,8	2		
PEQ7	Gain [dB]		+3 dB		
	Frequency [Hz]		16000 Hz		
	Slope [Bw]		0,8		
PEQ8	Gain [dB]				
	Frequency [Hz]				
	Slope [Bw]				

		Stinger 10G3 SAT	Stinger 10G3 FR	Stinger 10G3 MON	Stinger 10G3 FLT
GAIN	dB	0	0	0	0
Delay	Time (ms)	0	0	0	0
High Pass	Frequency [Hz]	95 Hz	50 Hz	90 Hz	50 Hz
	Slope [Bw]	24 dB/oct BW	24 dB/oct BW	24 dB/oct BW	24 dB/oct BW
Low Pass	Frequency				
	Slope				
PEQ1	Gain [dB]	+ 3 dB	+ 3 dB	-1 dB	+ 3 dB
	Frequency [Hz]	65 Hz	55 Hz	150 Hz	65 Hz
	Slope [Bw]	3	0,7	2	2
PEQ2	Gain [dB]	-1 dB	+ 6 dB	-2 dB	-1 dB
	Frequency [Hz]	150 Hz	65 Hz	1500 Hz	150 Hz
	Slope [Bw]	2	2	1,4	2
PEQ3	Gain [dB]	-2 dB	-1 dB	-2 dB	-2 dB
	Frequency [Hz]	1500 Hz	150 Hz	4000 Hz	1500 Hz
	Slope [Bw]	1,4	2	7	1,4
PEQ4	Gain [dB]	-2 dB	-2 dB	+2 dB	+2 dB
	Frequency [Hz]	4000 Hz	1500 Hz	3000 Hz	3000 Hz
	Slope [Bw]	7	1,4	2	0,9
PEQ5	Gain [dB]	-2 dB	-2 dB	-2 dB	-2 dB
	Frequency [Hz]	6500 Hz	4000 Hz	6500 Hz	4000 Hz
	Slope [Bw]	5	7	5	7
PEQ6	Gain [dB]	+ 3 dB	-2 dB	-9 dB	-2 dB
	Frequency [Hz]	15000 Hz	6500 Hz	19000 Hz	6500 Hz
	Slope [Bw]	0,8	5	0,7	5
High Shelf - 2 dB	Gain [dB]		+ 3 dB		-6 dB
	Frequency [Hz]	310 Hz	15000 Hz		18000 Hz
	Slope [Bw]	-	0,8		3,1
High Shelf - 2 dB	Gain [dB]		High Shelf - 2 dB		
	Frequency [Hz]		310 Hz		
	Slope [Bw]		-		

DSP PARAMETER LD STINGER G3 SERIES



		Stinger 12G3 SAT	Stinger 12G3 FR	Stinger 12G3 MON	Stinger 12G3 FLT
GAIN	dB	0	0	0	0
Delay	Time (ms)	0	0	0	0
High Pass	Frequency [Hz]	95 Hz	45 Hz	80 Hz	45 Hz
	Slope [Bw]	24 dB/oct BW	24 dB/oct BW	24 dB/oct BW	24 dB/oct BW
Low Pass	Frequency				
	Slope				
PEQ1	Gain [dB]	-1 dB	+ 8 dB	+ 4 dB	+ 4 dB
	Frequency [Hz]	600 Hz	42 Hz	65 Hz	65 Hz
	Slope [Bw]	2	0,7	1	1
PEQ2	Gain [dB]	-2 dB	+ 9 dB	-1 dB	-1 dB
	Frequency [Hz]	1100 Hz	65 Hz	600 Hz	600 Hz
	Slope [Bw]	6	1	2	2
PEQ3	Gain [dB]	-2 dB	-1 dB	-4 dB	-4 dB
	Frequency [Hz]	4500 Hz	200 Hz	1140 Hz	1140 Hz
	Slope [Bw]	3	0,7	8	8
PEQ4	Gain [dB]	+3 dB	-1 dB	+ 3 dB	+ 3 dB
	Frequency [Hz]	15000 Hz	600 Hz	2000 Hz	2000 Hz
	Slope [Bw]	0,7	2	0,7	0,7
PEQ5	Gain [dB]	High Shelf + 1 dB	-2 dB	- 3 dB	- 3 dB
	Frequency [Hz]	4400 Hz	1140 Hz	4500 Hz	4500 Hz
	Slope [Bw]	-	6	3	3
PEQ6	Gain [dB]		-2 dB	-6 dB	+ 4 dB
	Frequency [Hz]		4500 Hz	19000 Hz	5200 Hz
	Slope [Bw]		3	1,4	3
PEQ7	Gain [dB]		+ 3 dB		+ 2 dB
	Frequency [Hz]		15000 Hz		14000 Hz
	Slope [Bw]		0,7		3
PEQ8	Gain [dB]		High Shelf + 1 dB		High Shelf + 2 dB
	Frequency [Hz]		4400		3000 Hz
	Slope [Bw]		-		-

		Stinger 15G3 SAT	Stinger 15G3 FR	Stinger 15G3 MON	Stinger 15G3 FLT
GAIN	dB	0	0	0	0
Delay	Time (ms)	0	0	0	0
High Pass	Frequency [Hz]	95 Hz	40 Hz	55 Hz	40 Hz
	Slope [Bw]	24 dB/oct BW	24 dB/oct BW	24 dB/oct BW	24 dB/oct BW
Low Pass	Frequency				
	Slope				
PEQ1	Gain [dB]	+ 3 dB	+ 8 dB	+ 4 dB	+ 4 dB
	Frequency [Hz]	65 Hz	42 Hz	65 Hz	65 Hz
	Slope [Bw]	3	0,7	1	1
PEQ2	Gain [dB]	-2 dB	+ 9 dB	-3 dB	-1 dB
	Frequency [Hz]	250 Hz	65 Hz	250 Hz	250 Hz
	Slope [Bw]	6	1	2	2
PEQ3	Gain [dB]	-2 dB	+ 2 dB	-3 dB	-3 dB
	Frequency [Hz]	600 Hz	200 Hz	600 Hz	600 Hz
	Slope [Bw]	4	0,7	4	4
PEQ4	Gain [dB]	-3 dB	-1 dB	-3 dB	-3 dB
	Frequency [Hz]	900 Hz	250 Hz	900 Hz	900 Hz
	Slope [Bw]	2	6	2	2
PEQ5	Gain [dB]	+ 6 dB	-3 dB	+ 4 dB	+ 4 dB
	Frequency [Hz]	15000 Hz	600 Hz	2200 Hz	2200 Hz
	Slope [Bw]	1,2	4	0,7	0,7
PEQ6	Gain [dB]	High Shelf + 3 dB	-3 dB	- 4 dB	+ 5 dB
	Frequency [Hz]	1900 Hz	900 Hz	19000 Hz	14000 Hz
	Slope [Bw]		2	1,6	1
PEQ7	Gain [dB]		+ 6 dB	High Shelf + 3 dB	High Shelf + 3 dB
	Frequency [Hz]		15000 Hz	1685 Hz	1685 Hz
	Slope [Bw]		1,2	-	-
PEQ8	Gain [dB]		High Shelf + 3 dB		
	Frequency [Hz]		1900 Hz		
	Slope [Bw]		-		

DSP PARAMETER LD STINGER G3 SERIES



		Stinger SUB15G3	Stinger SUB18G3	STINGER 28G3 SAT	STINGER 28G3 FR	STINGER 28G3 MON	STINGER 28G3 FLT
GAIN	dB	0	0	0	0	0	0
Delay	Time (ms)	0	0	0	0	0	0
High Pass	Frequency [Hz]	33 Hz	30 Hz	95 Hz	55 Hz	55 Hz	55 Hz
	Slope [Bw]	24 dB/oct BW	24 dB/oct BW	24 dB/oct BW	24 dB/oct BW	24 dB/oct BW	24 dB/oct BW
Low Pass	Frequency	100 Hz	105 Hz				
	Slope	24 dB/oct BW	24 dB/oct BW				
PEQ1	Gain [dB]	+ 4 dB	+ 6 dB	+6 dB	+5 dB	+8 dB	+5 dB
	Frequency [Hz]	42 Hz	37 Hz	65 Hz	55 Hz	65 Hz	65 Hz
	Slope [Bw]	1	0,9	1	0,8	1	1
PEQ2	Gain [dB]	+ 3 dB	+ 3 dB	-1 dB	+9 dB	+2 dB	+2 dB
	Frequency [Hz]	65 Hz	65 Hz	1000 Hz	65 Hz	180	180
	Slope [Bw]	3	3	6	1	1,6	1,6
PEQ3	Gain [dB]			- 3 dB	-1 dB	-4 dB	-4 dB
	Frequency [Hz]			1185 Hz	1000 Hz	310 Hz	310 Hz
	Slope [Bw]			1,5	6	1,6	1,6
PEQ4	Gain [dB]			- 3 dB	- 3 dB	-1 dB	-1 dB
	Frequency [Hz]			3000 Hz	1185 Hz	1000 Hz	1000 Hz
	Slope [Bw]			3,4	1,5	6	6
PEQ5	Gain [dB]			+2 dB	- 3 dB	- 3 dB	- 3 dB
	Frequency [Hz]			5500 Hz	3000 Hz	1185 Hz	1185 Hz
	Slope [Bw]			5,3	3,4	1,5	1,5
PEQ6	Gain [dB]			- 2 dB	+2 dB	+3 dB	+3 dB
	Frequency [Hz]			6500 Hz	5500 Hz	2200 Hz	2200 Hz
	Slope [Bw]			4,5	5,3	0,6	0,6
PEQ7	Gain [dB]			+4 dB	- 2 dB	- 1 dB	- 1 dB
	Frequency [Hz]			15000 Hz	6500 Hz	2500	2500
	Slope [Bw]			1,3	4,5	3	3
PEQ8	Gain [dB]				+4 dB	- 3 dB	- 3 dB
	Frequency [Hz]				15000 Hz	3000 Hz	3000 Hz
	Slope [Bw]				1,3	3,4	3,4
PEQ9	Gain [dB]					+2 dB	+2 dB
	Frequency [Hz]					5500 Hz	5500 Hz
	Slope [Bw]					5,3	5,3
PEQ10	Gain [dB]					- 2 dB	- 2 dB
	Frequency [Hz]					6500 Hz	6500 Hz
	Slope [Bw]					4,5	4,5